

POWERBANK 10



Power Beyond Limits
Coming Soon.

BETA SPECIFICATION

POWERBANK 10

10.1 kWh MODULAR BATTERY

SYSTEM SPECIFICATION	
Nominal Output Power	5000 W
Capacity Range	10.1 ~ 60.5 kWh (95% DoD)
Battery Chemistry	LFP (LiFePO4)
IP Protection	IP65 (Outdoor)
System Dimension (W x D x H)	610 x 250 x 1161 mm (with Bracket)
System Weight	109.5 kg
Warranty	10 Year Full Replacement Warranty

INVERTER TECHNICAL SPECIFICATION	
Model	REA-INV-5
Coupling	AC Coupled
Max. Charging/Discharging Current	60 A
Max. Charging/Discharging Power	5000 W
Rated Frequency	50 / 60 Hz
Rated Voltage	230 V
Rated Output Apparent Power (Grid Port)	5000 VA
Rated Output Apparent Power (Backup Port)	5000 VA
Max. AC input Power (Grid Port)	10000 W
Rated Output Current (Grid Port)	21.7 A
Max. AC Output Current (Grid Port)	21.7 A
Rated Output Current (Backup Port)	21.7 A
Max. AC Output Current (Backup Port)	21.7 A
Max Inverter Efficiency	97.3%
Backup	UPS
Communication	Ethernet / WiFi
Humidity	0~90% (No Condensing)
Dimension (W x D x H)	610 x 212 x 366 mm
Weight	19.5 kg
Safety	IEC 62109, IEC 62040
EMC	EN61000-6-1/-2 /-3/-4
Grid Regulation	AS4777.2

BATTERY TECHNICAL SPECIFICATION	
Module Mode	REA-BANK-10.1
Module Capacity	10.1 kWh
Usable Capacity	9.6 kWh
Depth of Discharge (DoD)	95%
Nominal Voltage	96 V
Battery Voltage Range	91.5 V ~ 106.5 V
Max. Charging/Discharging Current	60 A
Operating Temperature Range	-10°C ~ 50°C*
Cycle Life	10,000**
Battery Modules Connection	1 ~ 6 in Parallel

* Max. charge/discharge current derating will occur related to temperature and SOC.

** Under specific test conditions.



T&C: Product design and specifications included in this beta document are subject to change.

©2024 REA Power. All Rights Reserved.

Contact

Unit 6, 19 Lennox Street, Redland Bay, QLD 4165, Australia

PH: 1300 360 047

E: engineering@reapower.com.au

W: www.reapower.com.au

REA POWER™